

ZWBMD022022

Application: Optical device, Advertising rotating drive, Bank machines, and etc.

Standard Plastic Geared Motor

Output Power: 0.5W~4.5W

Metal output shaft

Model	Application Parameters							Overall Length mm	Rated Torque of Gear Box gf.cm	Instant Torque of Gear Box gf.cm	Gear Ratio	Gear Box Length mm
	Rated	At No Load		At Rated Load								
	Voltage	Speed	Current	Speed	Current 电流	Torque						
	VDC	rpm	mA	rpm	mA	gf.cm mN.m						
ZWBMD022022-4	24.0	1886	100	1675	295	160	15.7	57.5	17000	51000	4	19.1
ZWBMD022022-6	24.0	1258	100	1117	295	240	23.5		17000	51000	6	
ZWBMD022022-16	24.0	472	110	419	295	512	50.2	64.8	17000	51000	16	26.4
ZWBMD022022-24	24.0	314	110	279	295	768	75.3		17000	51000	24	
ZWBMD022022-36	24.0	210	110	186	295	1152	113.0		17000	51000	36	
ZWBMD022022-64	24.0	118	120	105	295	1350	132.4	72.1	17000	51000	64	33.7
ZWBMD022022-96	24.0	79	120	70	295	2025	198.6		17000	51000	96	
ZWBMD022022-144	24.0	52	120	47	295	3038	297.9		17000	51000	144	
ZWBMD022022-216	24.0	35	120	31	295	4556	446.8		17000	51000	216	
ZWBMD022022-256	24.0	28	120	26	300	4050	397.2	79.4	17000	51000	256	41
ZWBMD022022-384	24.0	19	120	17	300	6075	595.8		17000	51000	384	
ZWBMD022022-576	24.0	13	120	12	300	9113	893.7		17000	51000	576	
ZWBMD022022-864	24.0	8	120	8	300	13669	1340.5		17000	51000	864	
ZWBMD022022-1296	24.0	6	120	5	300	10000	980.7		17000	51000	1296	

* above specifications are subject to change without notice, just for reference and customizable according to requirements

